

IIS

Deployment Guide

UPDATED: 19 March 2021



Copyright Notices

Copyright © 2002-2021 Kemp Technologies, Inc. All rights reserved. Kemp Technologies and the Kemp Technologies logo are registered trademarks of Kemp Technologies, Inc.

Kemp Technologies, Inc. reserves all ownership rights for the LoadMaster and Kemp 360 product line including software and documentation.

Used, under license, U.S. Patent Nos. 6,473,802, 6,374,300, 8,392,563, 8,103,770, 7,831,712, 7,606,912, 7,346,695, 7,287,084 and 6,970,933



Table of Contents

1 Introduction	
1.1 Document Purpose	
1.2 Intended Audience	4
1.3 Related Firmware Version	
2 Template	5
3 Architecture	6
4 Configure the LoadMaster	7
4.1 Enable Subnet Originating Requests Globally	7
4.2 Enable Check Persist Globally	8
4.3 Create the IIS Virtual Services	8
4.3.1 Create an IIS HTTP Virtual Service	8
4.3.2 Create an IIS HTTPS Virtual Service	
4.3.3 Create an IIS HTTPS Offloaded Virtual Service	11
4.3.4 Create an IIS HTTPS Re-encrypt Virtual Service	
4.4 Create the IIS and WAF Virtual Services	15
4.4.1 Create an IIS HTTP and WAF Virtual Service	
4.4.2 Create an IIS HTTPS Offloaded and WAF Virtual Service	16
4.4.3 Create an IIS HTTPS Re-encrypt and WAF Virtual Service	
References	22
Last Updated Date	



1 Introduction

Internet Information Services (IIS, formerly Internet Information Server) is an extensible web server created by Microsoft for use with Windows NT family. IIS supports HTTP, HTTPS, FTP, FTPS, SMTP and NNTP. It has been an integral part of the Windows NT family since Windows NT 4.0, though it may be absent from some editions (for example, Windows XP Home edition), and is not active by default.

The Kemp LoadMaster is used to load balance the IIS workload. The LoadMaster offers advanced Layer 4 and Layer 7 server load balancing, SSL Acceleration and a multitude of other advanced Application Delivery Controller (ADC) features. The LoadMaster intelligently and efficiently distributes user traffic among the application servers so that users get the best experience possible.

1.1 Document Purpose

This document provides the recommended LoadMaster settings used when load balancing the IIS workload. The Kemp Support Team is available to provide solutions for scenarios not explicitly defined. The Kemp support site can be found at: <u>https://support.kemptechnologies.com</u>

1.2 Intended Audience

This document is intended to be read by anyone who is interested in configuring the LoadMaster to optimize the IIS server.

1.3 Related Firmware Version

Published with LMOS version 7.2.48.4 LTS. This document has not required substantial changes since 7.2.48.4 LTS. However, the content is in sync with the latest LoadMaster LTS firmware.



2 Template

Kemp has developed a template containing our recommended settings for this workload. You can install this template to help create Virtual Services (VSs) because it automatically populates the settings. You can use the template to easily create the required VSs with the recommended settings. For some workloads, additional manual steps may be required such as assigning a certificate or applying port following, these steps are covered in the document, if needed.

You can remove templates after use and this will not affect deployed services. If needed, you can make changes to any of the VS settings after using the template.

Download released templates from the Templates section on the Kemp Documentation page.

For more information and steps on how to import and use templates, refer to the <u>Virtual Services</u> and <u>Templates</u>, <u>Feature Description</u> on the Kemp Documentation page.

IIS 3 Architecture



3 Architecture





The deployed IIS environment determines which of the following setups is used.

4.1 Enable Subnet Originating Requests Globally

It is best practice to enable the **Subnet Originating Requests** option globally.

In a one-armed setup (where the Virtual Service and Real Servers are on the same network/subnet) **Subnet Originating Requests** is usually not needed. However, enabling **Subnet Originating Requests** should not affect the routing in a one-armed setup.

In a two-armed setup where the Virtual Service is on network/subnet A, for example, and the Real Servers are on network B, **Subnet Originating Requests** should be enabled on LoadMasters with firmware version 7.1-16 and above.



When **Subnet Originating Requests** is enabled, the Real Server sees traffic originating from 10.20.20.21 (LoadMaster eth1 address) and responds correctly in most scenarios.

With **Subnet Originating Requests** disabled, the Real Server sees traffic originating from 10.0.0.15 (LoadMaster Virtual Service address on **eth0**) and responds to **eth0** which could cause asymmetric routing.

When **Subnet Originating Requests** is enabled globally, it is automatically enabled on all Virtual Services. If the **Subnet Originating Requests** option is disabled globally, you can choose whether to enable **Subnet Originating Requests** on a per-Virtual Service basis.

To enable **Subnet Originating Requests** globally, follow the steps below:

1. In the main menu of the LoadMaster User Interface (UI), go to **System Configuration > Miscellaneous Options > Network Options**.

2. Select the **Subnet Originating Requests** check box.



4.2 Enable Check Persist Globally

It is recommended that you change the **Always Check Persist** option to **Yes – Accept Changes**. Use the following steps:

1. Go to System Configuration > Miscellaneous Options > L7 Configuration.

Allow connection scaling over 64K Connections	
Always Check Persist	Yes - Accept Changes 🗸
Add Port to Active Cookie	
Conform to RFC	
Close on Error	
Add Via Header In Cache Responses	
Real Servers are Local	
Drop Connections on RS failure	
Drop at Drain Time End	
L7 Connection Drain Time (secs)	300 Set Time (Valid values:0, 60 - 86400)
L7 Authentication Timeout (secs)	30 Set Timeout (Valid values:30 - 300)
L7 Client Token Timeout (secs)	120 Set Timeout (Valid values:60 - 300)
Additional L7 Header	X-Forwarded-For 🗸
100-Continue Handling	RFC-7231 Compliant 🗸
Allow Empty POSTs	
Allow Empty HTTP Headers	
Force Complete RS Match	
Least Connection Slow Start	0 Set Slow Start (Valid values:0 - 600)
Share SubVS Persistence	
Log Insight Message Split Interval	10 Set Log Split Interval (Valid values:1 - 100)
Include User Agent Header in User Logs	
NTLM Proxy Mode	

2. Click the Always Check Persist drop-down arrow and select Yes – Accept Changes.

Enable Check Persist is not required if active cookie is enabled.

4.3 Create the IIS Virtual Services

The following sections describe the recommended settings for the IIS Virtual Services.

4.3.1 Create an IIS HTTP Virtual Service

The following are the steps involved and the recommended settings to configure the IIS Virtual Service:

1. In the main menu of the LoadMaster Web User Interface (WUI), go to **Virtual Services > Add New**.

IIS



Please Specify the Parameters for the Virtual Service.		
Virtual Address	10.154.11.141	
Port	80	
Service Name (Optional)	IIS HTTP	
Use Template	Select a Template	
Protocol	tcp 🗸	
	Cancel Add this Virtual Service	

- 2. Type a valid Virtual Address.
- 3. Type **80** as the **Port**.
- 4. Enter a recognizable Service Name, such as IIS HTTP Virtual Service.
- 5. Click Add this Virtual Service.
- 6. Configure the settings as recommended in the following table:

Section	Option	Value	Comment
Standard Options	Timeout	1 Hour	
	Cookie name	JSESSIONID	
	Scheduling Method	least connection	

- 7. Add the Real Servers:
- 8. Expand the **Real Servers** section.
- 9. Click Add New.
 - a) Enter the address of the relevant Real Server.
 - b) Complete the other fields as required.
 - c) Click Add this Real Server then click OK to the pop-up message.

d) Repeat the steps above to add more Real Servers as needed, based on your environment.



4.3.2 Create an IIS HTTPS Virtual Service

The following are the steps involved and the recommended settings to configure the IIS HTTPS Virtual Service:

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

Please Specify the	e Parameters for the Virtual Service.
Virtual Address	10.154.11.141
Port	443
Service Name (Optional)	IIS HTTPS
Use Template	Select a Template
Protocol	tcp 🗸
	Cancel Add this Virtual Service

- 2. Type a valid Virtual Address.
- 3. Type **443** as the **Port**.
- 4. Enter a recognizable **Service Name**, such as **IIS HTTPS Virtual Service**.
- 5. Click Add this Virtual Service.
- 6. Configure the settings as recommended in the following table:

Section	Option	Value	Comment
Standard Options	Persistence Mode	Source IP Address	
	Timeout	1 Hour	
	Scheduling Method	least connection	
	Idle Connection Timeout	900	
Advanced Properties	Add a Port 80 Redirector VS	https://%h%s	Click Add HTTP Redirector . This automatically creates a redirect on port 80.



Section	Option	Value	Comment
Real Servers	URL	/	

- 7. Add the Real Servers:
- 8. Expand the **Real Servers** section.
- 9. Click Add New.
 - a) Enter the address of the relevant Real Server.
 - b) Complete the other fields as required.
 - c) Click Add this Real Server then click OK to the pop-up message.

d) Repeat the steps above to add more Real Servers as needed, based on your environment.

Create an IIS HTTPS Redirect Virtual Service

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Real Server Check Method** and **Persistence Mode** to **None**.

4.3.3 Create an IIS HTTPS Offloaded Virtual Service

The following are the steps involved and the recommended settings to configure the IIS HTTPS Offloaded Virtual Service:

Virtual Address	10.154.11.143	
Port	443	
Service Name (Optional)	IIS HTTPS Offloaded	
Use Template	Select a Template	
Protocol	tcp 🗸	
	Cancel Add this Virtual Service	

1. In the main menu of the LoadMaster WUI, go to **Virtual Services > Add New**.

IIS



- 2. Type a valid Virtual Address.
- 3. Type **443** as the **Port**.
- 4. Enter a recognizable **Service Name**, such as **IIS HTTPS Offloaded HTTP** Virtual Service.
- 5. Click Add this Virtual Service.
- 6. Configure the settings as recommended in the following table:

Section	Option	Value	Comment
Standard Options	Persistence Mode	Active Cookie	SSL Acceleration must be enabled before you can select Active Cookie as a Persistence Mode.
	Timeout	1 Hour	
	Scheduling Method	least connection	
	Idle Connection Timeout	900	
SSL Properties	SSL Acceleration	Enabled	
	Cipher Set	BestPractices	
Advanced Properties	Add a Port 80 Redirector VS	https://%h%s	Click Add HTTP Redirector . This automatically creates a redirect on port 80.
Real Servers	Real Server Check Method	HTTPS Protocol	
	URL	/	

7. Add the Real Servers:

8. Expand the **Real Servers** section.

9. Click Add New.

- a) Enter the address of the relevant Real Server.
- b) Complete the other fields as required.
- c) Click Add this Real Server then click OK to the pop-up message.



d) Repeat the steps above to add more Real Servers as needed, based on your environment.

Create an IIS HTTPS Offloaded Redirect Virtual Service

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Real Server Check Method** and **Persistence Mode** to **None**.

4.3.4 Create an IIS HTTPS Re-encrypt Virtual Service

The following are the steps involved and the recommended settings to configure the IIS HTTPS Reencrypt Virtual Service:

1. In the main menu of the LoadMaster WUI, go to Virtual Service	<pre>> Add New.</pre>
--	--------------------------

Please Specify the	e Parameters for t	the	Virtual	Service.
Virtual Address	10.154.11.143			
Port	443			
Service Name (Optional)	IIS HTTPS Re-encry			
Use Template	Select a Template	\sim		
Protocol	tcp 🗸			
			Cancel	Add this Virtual Service

- 2. Type a valid Virtual Address.
- 3. Type **443** as the **Port**.
- 4. Enter a recognizable **Service Name**, such as IIS HTTPS Re-encrypt Virtual Service.
- 5. Click Add this Virtual Service.
- 6. Configure the settings as recommended in the following table:

Section	Option	Value	Comment
Standard Options	Persistence Mode	Active Cookie	SSL Acceleration must be enabled before you can select Active Cookie as a Persistence Mode.

kemp.ax



Section	Option	Value	Comment
	Timeout	1 Hour	
	Cookie name	JSESSSIONID	
	Scheduling Method	least connection	
	Idle Connection Timeout	900	
SSL Properties	SSL Acceleration	Enabled	
	Reencrypt	Enabled	
	Cipher Set	Best Practices	
Advanced Properties	Add a Port 80 Redirector VS	https://%h%s	Click Add HTTP Redirector . This automatically creates a redirect on port 80.
Real Servers	URL	/	

7. Add the Real Servers:

8. Expand the **Real Servers** section.

9. Click Add New.

- a) Enter the address of the relevant Real Server.
- b) Complete the other fields as required.
- c) Click Add this Real Server then click OK to the pop-up message.

d) Repeat the steps above to add more Real Servers as needed, based on your environment.

Create an IIS HTTPS Re-encrypt Redirect Virtual Service

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Real Server Check Method** and **Persistence Mode** to **None**.

kemp.ax



4.4 Create the IIS and WAF Virtual Services

The following sections describe the recommended settings for the IIS and WAF Virtual Services.

4.4.1 Create an IIS HTTP and WAF Virtual Service

The following are the steps involved and the recommended settings to configure the IIS HTTP WAF Virtual Service:

1. In the main menu of the LoadMaster WUI, go to Virtual Services > Add New.

Please Specify the	e Parameters for the Virtual Service.
Virtual Address	10.154.11.144
Port	80
Service Name (Optional)	IIS HTTP and WAF
Use Template	Select a Template
Protocol	tcp 🗸
	Cancel Add this Virtual Service

- 2. Type a valid Virtual Address.
- 3. Type **80** as the **Port**.
- 4. Enter a recognizable **Service Name**, such as IIS HTTP WAF Virtual Service.
- 5. Click Add this Virtual Service.
- 6. Configure the settings as recommended in the following table:

Section	Option	Value
Standard Options	Persistence Mode	Source IP Address
	Timeout	6 Minutes
	Scheduling Method	least connection
WAF Options	Enabled	Yes
	Default Operation	Block Mode

kemp.ax



Section	Option	Value
	Audit mode	Audit Relevant
	Enabled Rules	owasp_protocol_violations
		owasp_protocol_anomalies
		owasp_request_limits
		owasp_bad_robots
		owasp_generic_attacks
		owasp_xss_attacks
		owasp trojans
		owasp_common_exceptions
	Application Specific	iis_attacks
Real Servers	Real Server Check Method	HTTPS Protocol
Real Servers	URL	/

- 7. Add the Real Servers:
- 8. Expand the **Real Servers** section.
- 9. Click Add New.
 - a) Enter the address of the relevant Real Server.
 - b) Complete the other fields as required.
 - c) Click Add this Real Server then click OK to the pop-up message.

d) Repeat the steps above to add more Real Servers as needed, based on your environment.

4.4.2 Create an IIS HTTPS Offloaded and WAF Virtual Service

The following are the steps involved and the recommended settings to configure the IIS HTTPS Offloaded and WAF Virtual Service:

1. In the main menu of the LoadMaster WUI, go to Virtual Services > Add New.

IIS

Please Specify the Parameters for the Virtual Service.				
Virtual Address	10.154.11.144			
Port	443			
Service Name (Optional)	IIS HTTPS Offloaded			
Use Template	Select a Template			
Protocol	tcp 🗸			
	Cancel Add this Virtual Service			

- 2. Type a valid Virtual Address.
- 3. Type **443** as the **Port**.
- 4. Enter a recognizable **Service Name**, such as IIS HTTPS Offloaded WAF Virtual Service.
- 5. Click Add this Virtual Service.
- 6. Configure the settings as recommended in the following table:

Section	Option	Value	Comments
Standard Options	Persistence Mode	Source IP Address	
	Timeout	6 Minutes	
	Scheduling Method	least connection	
	Idle Connection Timeout	900	
SSL Properties	Enabled	Selected	
	Cipher Set	Best Practices	
Advanced Properties	Add a Port 80 Redirector VS	https://%h%s	Click Add HTTP Redirector . This automatically creates a redirect on port 80.
WAF Options	Enabled	Yes	

kemp.ax



Section	Option	Value	Comments
	Default Operation	Block Mode	
	Audit Mode	Audit Relevant	
	Enabled Rules	owasp_protocol_ violations	
		owasp_protocol_ anomalies	
		owasp_request_ limits	
		owasp_bad_ robots	
		owasp_generic_ attacks	
		owasp_xss_ attacks	
		owasp_trojans	
		owasp_ common_ exceptions	
	Application Specific	iis_attacks	
Real Servers	Real Server Check Method	HTTPS Protocol	
Real Servers	URL	/	

7. Add the Real Servers:

8. Expand the **Real Servers** section.

9. Click Add New.

- a) Enter the address of the relevant Real Server.
- b) Complete the other fields as required.

kemp.ax



c) Click Add this Real Server then click OK to the pop-up message.

d) Repeat the steps above to add more Real Servers as needed, based on your environment.

Create an IIS HTTPS Offloaded and WAF Redirect Virtual Service

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Real Server Check Method** and **Persistence Mode** to **None**.

4.4.3 Create an IIS HTTPS Re-encrypt and WAF Virtual Service

The following are the steps involved and the recommended settings to configure the IIS HTTPS Reencrypt and WAF Virtual Service:

Virtual Address	10.154.11.144
Port	443
Service Name (Optional)	IIS HTTPS Re-encry
Use Template	Select a Template
Protocol	tcn 🖂

1. In the main menu of the LoadMaster WUI, go to Virtual Services > Add New.

- 2. Type a valid Virtual Address.
- 3. Type **443** as the **Port**.

4. Enter a recognizable **Service Name**, such as IIS HTTPS Re-encrypt and WAF Virtual Service.

- 5. Click Add this Virtual Service.
- 6. Configure the settings as recommended in the following table:



Section	Option	Value	Comments
Standard Options	Persistence Mode	Source IP Address	
	Timeout	6 Minutes	
	Scheduling Method	least connection	
	Idle Connection Timeout	900	
SSL Properties	Enabled	Selected	
	Reencrypt	Selected	
	Cipher Set	Best Practices	
Advanced Properties	Add a Port 80 Redirector VS	https://%h%s	Click Add HTTP Redirector . This automatically creates a redirect on port 80.
WAF Options	Enabled	Yes	
	Default Operation	Block Mode	
	Audit mode	Audit Relevant	
	Enabled Rules	owasp_protocol_ violations	
		owasp_protocol_ anomolies	
		owasp_request_ limits	
		owasp_bad_ robots	
		owasp_generic_ attacks	
		owasp_xss_	



Section	Option	Value	Comments
		attacks	
		owasp_trojans	
		owasp_ common_ exceptions	
	Application Specific	iis_attacks	
Real Servers	Real Server Check Method	HTTPS Protocol	
Real Servers	URL	/	

7. Add the Real Servers:

8. Expand the **Real Servers** section.

- 9. Click Add New.
 - a) Enter the address of the relevant Real Server.
 - b) Complete the other fields as required.
 - c) Click Add this Real Server then click OK to the pop-up message.

d) Repeat the steps above to add more Real Servers as needed, based on your environment.

Create an IIS HTTPS Re-encrypt and WAF Redirect Virtual Service

Clicking the **Add HTTP Redirector** button automatically creates a port 80 redirect Virtual Service. This is optional, but the purpose of this Virtual Service is to redirect any clients who have connected using HTTP to the HTTPS Virtual Service. Kemp also recommends changing the **Real Server Check Method** and **Persistence Mode** to **None**. **IIS** References



References

Unless otherwise specified, the following documents can be found at <u>http://kemptechnologies.com/documentation</u>.

Virtual Services and Templates, Feature Description



Last Updated Date

This document was last updated on 19 March 2021.

kemp.ax